

Barcode-reader

SUNMI 2D Handheld Scanner

- Equipped with a high-performance imaging chip, that captures even the shakiest frames, this scanner has a high motion tolerance that doesn't compromise on quality.
 - The ultra-quick decoding algorithm is the true definition of speed as it accurately identifies folded, colored and even distorted bar codes for easy accessibility.
 - The scanner briefly vibrates to let you know when a scan is complete so you never miss a code.
 - With looks that follow the latest design trends, the scanner enhances your store's image.
 - Comes with a three-year warranty (which even covers the built-in wire rods)
- *Does not cover physical damage



Scanning Barcode



Mobile Payment



















Drop-Proof



Plug and Play

SUNMI 2D Handheld Scanner

Technical specifications

 OS Windows/IOS Android/Linux	 Image sensor CMOS	 Pixel 640*480	 Reading precision ≥3mil	 Reading depth of field EAN13 (13mil) 55mm-300mm QR CODE (15mil) 35mm-190mm
 Lighting White LED	 External dimension 160*95*71mm	 Prompt method Buzzer, vibrator, LED prompt	 Focusing Red light LED 625nm	 Communication interface USB 2.0 TypeA male connector
 Field of view angle Horizontal 45° Vertical 34°	 Adapter Operating voltage: DC5V±5% Operating current: <500mA	 Symbol contrast ≥30%	 Environment Operating temperature: -10°C~50°C Storage temperature: -40°C~70°C Relative humidity: 5%-95% (no condensation) Electrostatic protection: ±8kV (direct discharge) ±15kV (air discharge) Drop height:1.2 meters	 Barcode sensitivity Inclined ±50° / Rotary 360° / Deflected ±50°
 Symbologies 1D: Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand 2D: PDF417, QR Code, Data Matrix				



DATASYSTEM

soluzioni per il retail

DATA SYSTEM srl

Sede e uffici amministrativi:

Via Santa Gilla, 51/b - 09122 Cagliari
tel. +39 070 288081 - fax +39 070 272151
www.datasystempos.it - info@datasystempos.it